



I2F MEDIA PRODUCTS

I2F MediaBox

Our software products are installed on an *MCS (Media Control Server)*, a name for standard hardware that answers to certain minimal standards for an optimal reproduction of media and a simultaneous control of diverse hardware.

We have now created **I2F MediaBox**, our own MCS, in two practical form factors. Surplus values are:

- ✓ Optional extension piece (CPE) for securing cable ends and connectors
- ✓ Easy to fix to a wall or table in any chosen orientation
- ✓ High quality components that follow closely the technological evolution. They guarantee a fast and steady performance and make sure that *real high def video* is not just hot air.

I2F MediaBox has been designed to operate 365 days a year in an unmanned way. We supply it completely with hard- and software according to your needs and budget, if desired with a pre-programmed media presentation.

Technical data for edition 01/2009:

	microATX (W 335 x D 255 x H 91 mm)	minilTX (W 275 x D 188 x H 75 mm)
Motherboard	ASUS microATX P5N7A-VL HDMI LGA775 NVIDIA GeForce 9300 (MCP7A-S) nForce730i 4DDR2	Intel Desktop Motherboard Media, BOXDG45FC, mini-ITX, G45 chipset, FSB1333MHz 800, Intel® X4500HD, no PCIe x16 graphics: DVI-I + HDMI, GbE, RAID 0,1,5,10 & Matrix, 8-ch audio
Processor	Boxed Intel® Core™2 Duo E8400 (6M Cache, 3.00 GHz, 1333 MHz FSB) LGA775	
HD	Transcend Desktop Memory 32GB Solid State Drive SATA MLC 2.5"	
Internal memory	Kingston HyperX memory 2GB 1066MHz DDR2 Non-ECC CL5 (5-5-5-15) DIMM	
Power supply	HEC-300FE-2RX 300 Watt high efficiency power supply	Seasonic SS-250SU APFC F0
5 Volt & 12 Volt available for peripherals through Phoenix connector		
Options	diverse i/o breakouts such as DMX, serial connections ... CPE (cable protection extension): D 82 mm	



Download the brochure I2F Media Products from www.inter2face.com

Inter2Face bvba Pelgrimstraat 9/4 B-3000 Leuven Belgium www.inter2face.com
Tel. +32 (0)16 205543 mediapro@inter2face.eu